

[Find by Feature](#)
[Browse by Category](#)
[Share](#)
 Search →

Enter part number or keyword

[Search Results \(129\)](#)
[Search Options](#)

129 Results:

1 2 3 4 ▶

[Compare](#)

12047767 Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm²


[12047767 FLRY-B 0,75 to 1,0 S](#)


[12047767 FLU142Y 0,75 to 1,0 S](#)
[10719093 ASM CONN 2 F M/P 150 BLK SLD](#)
[10718786 CONN 2 F M/P 150 NAT SLD](#)
[10721222 CONN 2 F M/P 150 GRA SLD](#)
[12045895 CONN 4 F M/P 150 280 SLD](#)
[12047867 CONN 4 F M/P 150 BLK](#)
[12059555 CONN 4 F M/P 150 GRA MD](#)
[12064843 CONN 26 F M/P 150 280](#)
[Compare](#)

1 2 3 4 ▶

Keyword: 12047767

[Edit Search Options](#)

Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm² Part #12047767


[Attributes](#)
[Documents \(10\)](#)

Part #:	12047767
Description:	Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm ²
Product Type:	Terminal
Status:	Active
Blade size [mm]:	1.5
Terminal family:	Metri-Pack
Series:	150
Gender:	Female
Sealed:	Unsealed
Plating:	Tin
Minimum Cable Core Cross Section [mm²]:	0.80
Maximum Cable Core Cross Section [mm²]:	1.00
Minimum Cable Diameter [mm]:	1.70
Maximum Cable Diameter [mm]:	2.40
Current range [A]:	14
Temperature range []:	-40 to 125

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.