



Rated Value : DC30V 0.1A
 Operating force : 320±80gf
 Mechanical life : 100,000 Cycles
 Operating Temp : -20°C To +80°C
 Contact Resistance : 200mΩ Max
 Insulation Resistance : 100MΩ Min
 Withstand Voltage : AC 250V(50HZ)/min
 Operating Type : Push To Lock (SL)
 Push No Lock (NL)



CIRCUIT DIAGRAM



P.C.B LAYOUT

⑦	Crochet Hook	1	Carbon Steel(SL)	Ecru
⑥	Terminals	6	Brass T=0.35mm	Ag plated
⑤	Housing	1	PBT	
④	Spring	1	Carbon Steel	Ecru
③	Contact Chip	2	Phosphor Brass	Ag plated
②	Keypad	1	POM	
①	Panel	1	POM	
NO.	PART NAME	Q'TY	MATERIAL	DESCRIPTION

MODEL: PBS-2201		DRAWN BY : Leiqin		DATE:	
TITLE : PUSH SWITCH		CHECKED BY : Liwei		DATE:	
DRAWING NO:		REV. : A		APPROVED BY: Wuxin	
SHEET: 1 OF 1		SCALE: 4:1		SIZE: A4 UNIT : mm	

GENERAL TOLERANCE:
 (UNLESS SPECIFIED)
 X. ±0.30mm X.* ± 3'
 X.X ±0.25mm X.X* ± 2'
 X.XX ±0.20mm X.XX* ± 1'
 X.XXX±0.10mm X.XXX* ± 0.5'

MEASURE POINT:
 QUADRANT POINT (QP)
 TANGENCY POINT (TP)
 INTERSECTION POINT (IP)

NO:	PARTICULAR	BY	DATE
1			
REVISIONS			



深圳市吉威电子有限公司
深圳市元吉威电子有限公司