

Interface module - VIP-2/SC/D15SUB/M/LED - 2322155

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




VARIOFACE module, with screw connection and D-Subminiature pin strip, for mounting on NS 35 rails, with LED, 15-pos.

Why buy this product

- 9 to 50-pos.
- Metal foot
- According to IEC 60603-13
- 1:1 connection
- Screw connection



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 451772
GTIN	4046356451772
Weight per Piece (excluding packing)	120.000 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	50 mm
Height	65.5 mm
Depth	45.1 mm

Ambient conditions

Interface module - VIP-2/SC/D15SUB/M/LED - 2322155

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	24 V DC
Max. perm. current (per branch)	2.5 A
Number of positions	15
Status display	LED
Mounting position	any

Connection data for connection 1

Connection name	Field level
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Connection data for connection 2

Connection name	Controller level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	15

Standards and Regulations

Connection in acc. with standard	CUL
Standards/regulations	IEC 60664
	DIN EN 50178
Degree of pollution	2
Overvoltage category	II

Approvals

Approvals

Approvals


UL Recognized / cUL Recognized / CSA / EAC / EAC / cULus Recognized


Interface module - VIP-2/SC/D15SUB/M/LED - 2322155


Approvals


Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
mm ² /AWG/kcmil	30-12		
Nominal current I _N	2 A		
Nominal voltage U _N	24 V		

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
mm ² /AWG/kcmil	30-12		
Nominal current I _N	2 A		
Nominal voltage U _N	24 V		

CSA		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	2122203
mm ² /AWG/kcmil	28-12		
Nominal current I _N	2 A		
Nominal voltage U _N	24 V		

EAC		7500651.22.01.00246	
-----	---	---------------------	--

EAC		RU C- DE.A*30.B.01742	
-----	---	--------------------------	--

Interface module - VIP-2/SC/D15SUB/M/LED - 2322155

Approvals

cULus Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>