

**1N4001 THRU 1N4007**  
GENERAL PURPOSE RECTIFIERS



<b>VOLTAGE:</b> 50~1000 Volts	<b>CURRENT:</b> 1 Amper	<b>Package:</b> DO-41	<b>Marking And Polarity</b>
-------------------------------	-------------------------	-----------------------	-----------------------------

**FEATURES**

- Glass Passivated Chip Junction
- Low Forward Voltage Drop For High Efficiency
- Low Leakage Current For High Reliability
- High Forward Surge Capability For High Reliability

**MECHANICAL DATA**

- **Package:** Molding Compound Meets UL 94 V-0 Flammability Rating, RoHS-Compliant
- **Polarity:** As Marked On Case
- **Mounting Position:** Any
- **Weight:** App. 0.208 Grams (0.00733 Ounce)

**TYPICAL APPLICATIONS**

- General Purpose Use In AC/DC Bridge Full Waverectification For PD, Adapter, Power Supply, Monitor, LED Driver, Printer, Audio Equipment, TV And Home appliances Etc. Applications.

**Remark:**

- ①. NH=niuhang trademark
- ②. FF=niuhang trademark  
YWW=Internal code, According to actual changes
- ③. 1N400X=Modle, x=1,2,3,4,5,6,7
- ④. White band denotes cathode

Single Phase, Half Wave, 60Hz, Resistive Or Inductive Load. For Capacitive Load, Derate Current By 20%

**Maximum Ratings (Ta=25°C Unless otherwise specified)**

Parameter	Test Conditions	Symbol	1N	1N	1N	1N	1N	1N	1N	Unit
			4001	4002	4003	4004	4005	4006	4007	
Maximum Repetitive Peak Reverse Voltage		$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltag		$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage		$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current	@TC= 100 °C	$I_{F(AV)}$	1							A
Peak Forward Surge Current	8.3ms Single Half Sine-wave Superimposed On Rate Load	$I_{FSM}$	30							A
Current Squared Time Per Diode	t<8.3ms	$I^2t$	3.7							A

**Electrical Characteristics (Ta=25°C Unless otherwise specified)**

Parameter	Test Conditions	Symbol	1N	1N	1N	1N	1N	1N	1N	Unit
			4001	4002	4003	4004	4005	4006	4007	
Maximum Instaneous forward voltage per diode (note1)	Ta=25°C	$I_F = 1.0 A$	1.00							V
	Ta=125°C		0.92							
Maximum DC Reverse Current at Rated DC Blocking Voltage (Note 1)	Ta=25°C	$V_R = V_{RRM}$	5							uA
	Ta=125°C		$V_R = 80% * V_{RRM}$	500						
Typical Junction Capacitance Per Diode	4.0 V, 1MHz	$C_J$		15						

**Thermal Characteristics (Ta=25°C Unless otherwise specified)**

Parameter	Symbol	Ratings	Unit
Operating Junction Temperature Range	$T_J$	-55 to 150	°C
Storage Temperature Range	$T_{STD}$	-55 to 150	
Typical thermal resistance (Note 2)	$R_{\theta JA}$	50.0	°C/W
	$R_{\theta JC}$	18	

Notes: 1.Pulse Test: 300 Us Pulse Width, 2% Duty Cycle  
2.P. C. B mounted with 0.1\*\*0.1"(2.54 x 2.54 mm) copper Pad Areas

1N4001 THRU 1N4007  
GENERAL PURPOSE RECTIFIERS



Typical Characteristics Curves




Fig.1-FORWARD CURRENT DERATING CURVE




Fig.2- TYPICAL INSTANTANEOUS FORWARD




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL JUNCTION CAPACITANCE





Fig.5-MAX. NON-REPETITIVE SURGE CURRENT

**1N4001 THRU 1N4007**  
GENERAL PURPOSE RECTIFIERS



**OUTLINE DRAWINGS**

**DO-41**



**OUTLINE DIMENSIONS**

Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.0	-	2.8	0.079	-	0.110
B	25.1	-	28.0	0.988	-	1.102
C	0.6	-	0.9	0.024	-	0.035
D	4.2	-	5.2	0.165	-	0.205

**PACKING INFORMATION**

Package	Pack	Inner Box Size L×W×H(mm)	Quantity (pcs/Inner Box)	Outer Carton Size L×W×H(mm)	Quantity (pcs/carton)
DO-41	Braided/boxed	264x74x135	5000	420x280x310	50000

1N4001 THRU 1N4007


GENERAL PURPOSE RECTIFIERS



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )	3°C/second max.	3°C/second max.
Preheat -Temperature Min(T <sub>S</sub> min) -Temperature Max(T <sub>S</sub> max) -Time(t <sub>s</sub> min to t <sub>s</sub> max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (T <sub>L</sub> ) - Time (t <sub>L</sub> )	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(T <sub>P</sub> )	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t <sub>p</sub> )	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

**1N4001 THRU 1N4007**

GENERAL PURPOSE RECTIFIERS



**Disclaimer**

- Reproducing and modifying information of the document is prohibited without permission from niuhang Electronics co., LTD
- Niuhan Electronics co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhan Electronics co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhan can not notify