



**SPECIFICATIONS:**

- 1.VOLTAGE/CURRENT RATING: 30V/0.3A AC;
- 2.WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
- 3.INSULATION RESISTANCE: 50MΩ MIN;
- 4.CONTACT RESISTANCE: 100mΩ MAX;
- 5.OPERATING TEMPERATURE RANGE: -35° C TO 85° C.

**MATERIAL:**

- 1.INSULATOR: LCP UL 94V-0 BLACK;
- 2.TERMINAL: COPPER ALLOY;
- 3.METAL FITTINGS: COPPER ALLOY.

**PLATING:**

- 1.TERMINAL: GOLD PLATING, NICKEL 50u" MIN. OVER ALL;
- 2.METAL FITTINGS: TIN 100u" MIN. OVER NICKEL 50u"MIN.

PIN NO.	A	B	C
10	4.50	3.40	1.60
12	4.90	3.80	2.00
16	5.70	4.60	2.80
20	6.50	5.40	3.60
24	7.30	6.20	4.40
30	8.50	7.40	5.60
34	9.30	8.20	6.40
40	10.50	9.40	7.60
50	12.50	11.40	9.60



修订 SER	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE

CUSTOMER		<b>LXW</b> 连兴旺电子(深圳)有限公司 LXWCONN ELECTRONICS (SHENZHEN) CO., LTD	
一般公差 GENERAL TOLERANCE	制图 (DR): Kavin 2018.09.07	品名(TITLE): <b>BTB P0.40 SOCKET</b>	
.X ±0.25 .XX ±0.20 .XXX ±0.10 ANGLES ±1°	审核 (CHKD):	料号(PART NO): <b>LXW071S***</b>	
版本 (REV) A	比例(SCALE) 1:8	单位(UNITS) mm	张数(SHEET) 1 OF 1
核准 (APPD):		图幅 (SIZE) A4	